

Todo Collection
56 Inch Todo Fan BSS
 330025BSS (Brushed Stainless Steel)

Project Name: _____
 Location: _____
 Type: _____
 Qty: _____
 Comments: _____



Product Information

Product ID	330025BSS
Finish	Brushed Stainless Steel
Blade Finish	Brushed Stainless Steel
Collection	Todo Collection

Airflow, Power and Efficiency

Speed	RPM	CFM	CFM/ Watt	Amps	Watts
High	318	10642	112	.8	95
Med	253	8497	129	.73	66
Low	117	4130	227	.39	18

Dimensions



Downrod	A	B	C	D
1.00 OD X 8.00	15.00	12.25	7.50	5.25

Available Finishes

Finish	Fixture	Glass	Blade 1	Blade 2
Brushed Stainless Steel	330025BSS		BSS	

Specifications

Number of Blades	3
Blades Included	Yes
Blade Pitch	6.5 Degrees
Blade Sweep	56"
Blades Reversible	No
Blade Material	Steel
Optional Blades Available	No
Downrod 1	1.00 OD X 8.00
Primary Control System	4 Speed Wall Slide Control - In project applications using multiple ceiling fans, alternative remote controls may be required. Please contact Kichler Advanced Product Solutions at 844-542-4537 to confirm your project requirements.
Remote Included	No
Wall Control Included	Yes
Low Ceiling Adaptable	No
Lead Wire Length	78.00"
Motor Size	188MM X 20MM
Motor Type	AC INDUCTION

Downlight

Watts	95/66/18
Optional Light Kit Available	No

Safety Listings & Certifications

Safety Rated	Dry
Warranty	www.kichler.com/warranty

Todo Collection

56 Inch Todo Fan BSS

330025BSS (Brushed Stainless Steel)

Project Name: _____

Location: _____

Type: _____

Qty: _____

Comments: _____

Finish	Fixture	Glass	Blade 1	Blade 2
White	330025WH		WHITE	
Satin Black	330025SBK		SATIN BLACK	

Installation

Installation requirements

The electrical junction box and support structure must be securely mounted and capable of reliably supporting a minimum of 50 pounds. Use only ETL/UL listed electrical junction boxes marked ""For Fan Support""

Electrical Requirements 120V 60Hz AC

Hanging Weight 18.30 LBS

Minimum Distance Between Bottom Of Fan Blade To Floor 10 feet

Notes:

1) Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions.

2) Incandescent Equivalent: The incandescent equivalent as presented is an approximate number and is for reference only.